

Falling in Love

Falling in Love ist der verspielte Scheinwerfer aus hochwertigem Aluminium. Setze ein Objekt oder eine Wand brillant in Szene.

Mit Sunset Dimming (blaufreies Licht) schafft er eine gemütliche Atmosphäre und fördert den Schlaf. Der vielseitige LED-Strahler bietet eine perfekte Kombination aus Funktionalität und Stil für anspruchsvolle Beleuchtungskonzepte in jedem Raum.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben

Farben	Artikelnummer
● Black	FVD1-00
● Light Blue	FVD1-03
● Sand White	FVD1-05

Body

Maße Verpackung (L x B x H)	35cm x 25cm x 10cm
Material	Aluminium
Oberfläche	Pulverbeschichtet
Gewicht	1kg
Gewicht inkl. Verpackung	1,6kg
Leuchtenkopf beweglich	Ja
Montageart	Freistehend
Nennspannung	220–240V
Leistungsaufnahme	6W
Leuchteneffizienz	58lm/W
Länge Anschlussleitung	2,2m
Steckernetzteil	Ja
Artikelnummer	FVD1-00

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	350lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	Direkt
Abstrahlwinkel	54°
Lichtverteilung	Symmetrisch
Farbtemperatur	2700–1300K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Integrierter Taster

Falling in Love

Falling in Love is the playful spotlight made of high-quality aluminum. Set an object or a wall brilliantly in scene.

With Sunset Dimming (blue-free light), it creates a cozy atmosphere and supports healthy sleep. The versatile LED spotlight offers a perfect combination of functionality and style for sophisticated lighting concepts in every room.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
● Black	FVD1-00
● Light Blue	FVD1-03
● Sand White	FVD1-05

Body

Packaging dimensions (L x W x H)	35cm x 25cm x 10cm
Material	Aluminum
Surface	Powder-coated
Weight	1kg
Weight incl. packaging	1,6kg
Movable lamp head	Yes
Mounting type	Floor
Rated voltage	220–240V
Power consumption	6W
Luminaire efficiency	58lm/W
Length of connection cable	2,2m
Plug-in power supply unit	Yes
Protection class	II
SKU	FVD1-00

Light

Light source	LED
Luminous flux	350lm
Color rendering index	CRI >90
Light emission	Direct
Beam angle	54°
Light distribution	Symmetric
Color temperature	2700–1300K
Light color	Warm White
Dimmable	Yes
Type of dimming	Integrated pushbutton