

GRAU

Globe

Globe is the elegant aluminum ceiling light. It combines formal minimalism with a generous optical lens and provides a warm, uniform and glare-free light.

Globe is ideal for lighting bathrooms, entrance areas or living rooms. The high-quality design, the fine finishes and the brilliant lighting mood create a high-quality atmosphere in the room.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
 Polished	SE22-0
 Sand White	SE22-5
 White	SE22-3
 Black	SE22-2

Dimensions



Head
ø12 cm × H 8 cm

Body	Packaging dimensions (L x W x H)	30cm x 20cm x 14cm
	Material	Aluminum
	Surface	Polished
	Weight	0,9kg
	Weight incl. packaging	1,7kg
	Mounting type	Ceiling-mounted (surface)
	Rated voltage	220–240V
	Power consumption	12W
	Luminaire efficiency	78lm/W
	Connection cable (number of cores)	3
	Protection class	I
	SKU	SE22-0

Light	Light source	LED
	Luminous flux	930lm
	Color rendering index	CRI >90
	Light emission	Direct
	Beam angle	97°
	Light distribution	Symmetric
	Color temperature	2700K
	Light color	Warm White
	Dimmable	Yes
	Type of dimming	Trailing edge

GRAU

Globe

Globe is the elegant aluminum ceiling light. It combines formal minimalism with a generous optical lens and provides a warm, uniform and glare-free light.

Globe is ideal for lighting bathrooms, entrance areas or living rooms. The high-quality design, the fine finishes and the brilliant lighting mood create a high-quality atmosphere in the room.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
 Polished	SE22-0
 Sand White	SE22-5
 White	SE22-3
 Black	SE22-2

Dimensions



Head
Ø12 cm × H3,6 cm

Body	Mounting depth	110mm
	Mounting diameter	100mm
	Packaging dimensions (L x W x H)	22cm x 22cm x 17cm
	Material	Aluminum
	Surface	Powder-coated
	Weight	0,8kg
	Weight incl. packaging	1,2kg
	Mounting type	Ceiling-mounted (recessed)
	Rated voltage	220–240V
	Power consumption	12W
	Luminaire efficiency	78lm/W
	Connection cable (number of cores)	2
	Protection class	II
	SKU	SE20-2

Light	Light source	LED
	Luminous flux	930lm
	Color rendering index	CRI >90
	Light emission	Direct
	Beam angle	97°
	Light distribution	Symmetric
	Color temperature	2700K
	Light color	Warm White
	Dimmable	Yes
	Type of dimming	Trailing edge
	GRAU App upgrades possible	Yes
	Conversion to DALI possible	Yes