#### **Xt-a Ceiling**

Xt-a Ceiling is designed for open space lighting, such as conference rooms or hallways. The series combines clean, minimalist design with our patented OSA lighting technology.

Intuitive lighting control systems and glare control technology create a clear, comfortable and productive work environment.

Colors	Colors	SKU
	White/White	XA57-3
	Black/Black	XA57-2
	Satin/White	XA57-1
	Satin/Black	XA57-0

**Body** Pendant length 1m

Packaging dimensions (L x W x H) 194cm x 22cm x 17cm

Material Aluminum

Surface Powder-coated

Weight 5,5kg

Weight incl. packaging 9kg

Mounting type Pendant
Rated voltage 220–240V

Power consumption 89W

Luminaire efficiency 118lm/W

Connection cable (number of cores) 5

Protection class

SKU XA57-3

**Light** Light source LED

Luminous flux 10500lm

Direct color rendering index CRI >80

Indirect color rendering index CRI >80

Light emission 23% direct / 77% indirect

Light distribution Symmetric

Average LED life 50.000h

Color temperature 3500K

Light color Neutral White

Dimmable Yes

Type of dimming Pushbotton pulse (digital)

Motion sensor Yes
Range of the motion sensor 2m
Constant Light Regulator Yes
Sensor system can be switched off Yes
Status LED sensor Yes
Remote control included Yes

Swarm function Optional

#### **Xt-a Ceiling**

Xt-a Ceiling is designed for open space lighting, such as conference rooms or hallways. The series combines clean, minimalist design with our patented OSA lighting technology.

Intuitive lighting control systems and glare control technology create a clear, comfortable and productive work environment.

Colors	Colors	SKU
	White/White	XA57-3
	Black/Black	XA57-2
	Satin/White	XA57-1
	Satin/Black	XA57-0

#### **Dimensions**



**Body** Pendant length 1m

> Packaging dimensions (L x W x H) 194cm x 22cm x 17cm

Material Aluminum

Surface Powder-coated

Weight 5,5kg

Weight incl. packaging 9kg

Mounting type Pendant 220-240V Rated voltage

75W Power consumption

84lm/W Luminaire efficiency

Connection cable (number of cores) 5

Protection class Ī

SKU XA51-3

Light Light source LED

Light color

Luminous flux 6300lm

Direct color rendering index CRI >80

Indirect color rendering index CRI >80

62% direct / 38% indirect Light emission

Light distribution Symmetric Average LED life 50.000h 3500K

Color temperature

Dimmable

Type of dimming Pushbotton pulse (digital)

**Neutral White** 

Yes

Yes

Motion sensor Yes

Range of the motion sensor 2m

Constant Light Regulator Yes

Status LED sensor Yes

Sensor system can be switched off

Remote control included Yes

Swarm function Optional

#### **Xt-a Ceiling**

Xt-a Ceiling is designed for open space lighting, such as conference rooms or hallways. The series combines clean, minimalist design with our patented OSA lighting technology.

Intuitive lighting control systems and glare control technology create a clear, comfortable and productive work environment.

Colors	Colors	SKU
	White/White	XA57-3
	Black/Black	XA57-2
	Satin/White	XA57-1
	Satin/Black	XA57-0

#### **Dimensions**



Body Pendant length 1m

Packaging dimensions (L x W x H) 250cm x 22cm x 17cm

Material Aluminum

Surface Powder-coated

Weight 7,5kg

Weight incl. packaging 11kg

Mounting type Pendant

Rated voltage 220–240V

Power consumption 150W

Luminaire efficiency 107lm/W

Connection cable (number of cores) 5

Protection class I

SKU XA55-3

**Light** Light source LED

Luminous flux 16000lm

Direct color rendering index CRI >80

Indirect color rendering index CRI >80

Light emission 23% direct / 77% indirect

Light distribution Symmetric

Average LED life 50.000h

Color temperature 3500K

Light color Neutral White

Dimmable Yes

Type of dimming Pushbotton pulse (digital)

Motion sensor Yes

Range of the motion sensor 2m

Constant Light Regulator Yes

Sensor system can be switched off Yes

Status LED sensor Yes

Remote control included Yes

Swarm function Optional

#### **Xt-a Ceiling**

Xt-a Ceiling is designed for open space lighting, such as conference rooms or hallways. The series combines clean, minimalist design with our patented OSA lighting technology.

Intuitive lighting control systems and glare control technology create a clear, comfortable and productive work environment.

Colors	Colors	SKU
	White/White	XA57-3
	Black/Black	XA57-2
	Satin/White	XA57-1
	Satin/Black	XA57-0

Body Pendant length 1m

Packaging dimensions (L x W x H) 250cm x 22cm x 17cm

Material Aluminum

Surface Powder-coated

Weight 7,5kg

Weight incl. packaging 11kg

Mounting type Pendant

Rated voltage 220–240V

Power consumption 125W

Luminaire efficiency 72lm/W

Connection cable (number of cores) 5

Protection class

SKU XA53-3

**Light** Light source LED

Luminous flux 9000lm

Direct color rendering index CRI >80

Indirect color rendering index CRI >80

Light emission 62% direct / 38% indirect

Light distribution Symmetric

Average LED life 50.000h

Color temperature 3500K

Light color Neutral White

Dimmable Yes

Type of dimming Pushbotton pulse (digital)

Motion sensor Yes

Range of the motion sensor 2m

Constant Light Regulator Yes

Sensor system can be switched off Yes

Status LED sensor Yes

Remote control included Yes

Swarm function Optional